



FRESH-LOCK® Style 109 Soft Seal® Zipper The Fin-Seal Solution, Now Easier to Crush

- Now available in Presto's proprietary Soft Seal® material for a high-integrity side seal using less crushing energy
- Designed for machine-direction application to fin seal on vertical form/fill/seal equipment
- Requires less crushing time and/or temperature, allowing faster converting cycles
- Versatile style also works on horizontal form/fill/seal equipment
- Easy-to-crush material creates high-quality side seals that won't leak, gap or distort
- Coextruded sealant ribs enhance sealability and compatibility to a wide variety of films
- Wide offset flange provides gripping area for easy consumer opening
- Large spool size minimizes changeovers

Seal of Distinction

Applied to your package's fin seal area, the FRESH-LOCK® Style 109 zipper helps you lock in performance with only one machine-direction seal. Featuring patented sealant ribs, Style 109 not only seals at lower temperature for faster line speeds, but also seals to thinner films and reduces leaker rates. Style 109's proprietary sealant ribs maximize sealability to a variety of high-performance packaging films to ensure seal integrity. And whether you're packaging snacks or dairy products, pasta or pet food, Style 109 delivers the convenience features consumers prefer to give your package distinctive appeal. New Soft Seal® material enhances package quality.

Zipper Specification

Product Description:

STYLE 109 - Soft Seal® Material

GKL07418-1 Large Reusable Spool

GKL07518-1 Large Reusable Spool

PROFILE WEIGHT:

2.2 grams/ft +/- 0.1 grams/ft

WIDTH MEASUREMENTS:

16.0 mm +/- 1.0 mm

FOOTAGE/SPOOL:

12,000 ft + 100 - 0 ft

SPOOLS/PALLET:

10 spools

FOOTAGE/PALLET:

120,000 ft + 1000 - 0 ft

FINISHED SPOOL UNIT WEIGHT:

~65 lbs

PACKAGING:

Large Spool 15.81" width
 1.5" shaft O.D.
 23.50" flange O.D.

PROPERTIES:

Zipper material(s): Soft Seal® material with adhesive sealant
Suitable for food contact applications
Sealing temperature range: **220-300 °F
Holding force from consumer side: 1.5 lbs target avg.

POSITION OF ZIPPER:

The post next to interlocking members must be positioned toward the product/inside of package.

Each spool individually wrapped & placed in individual shipping case.

**Temperature range may vary depending on type of package film used.

Call your Fresh-Lock® zipper representative for details on our Zipper Spool Reuse Program.

www.Fresh-Lock.com



© 2008 Presto Products Company • A Business of Reynolds Packaging Group
P.O. Box 2399 • Appleton, WI 54912-2399
(800) 265-0750 • Fax (920) 738-1347 • E-mail: fresh-lock@reynoldspkg.com

