



FRESH-LOCK® Zipper Style 352 28.0mm Offset Zipper Versatile Zipper Design for Thermoform Applications

- This unique design provides a prime alternative for reclosable meat packages.
- Presto's proprietary Soft Seal® material provides a high-integrity side seal using less crushing energy.
- Design is engineered for the demands of a variety of flexible packaging applications.
- Pliable zipper profile feeds smoothly, seals cleanly in the thermoform fill & seal packaging process.
- Easy-lock single-track design allow consumers to feel the zipper seal tightly through the packaging film.
- Sealant layer enhances sealability and compatibility to a wide variety of package films.
- Lower sealing temperature that can allow faster line speeds.
- Colored locks are available in a variety of colors. See your FRESH-LOCK® salesperson for details.

Packed with Benefits for Processed Meat

- Presto's Style 352 Soft Seal® ME FRESH-LOCK® Zipper is a prime alternative for reclosable meat packages. It's packed with process-friendly features, like a pliable profile that feeds smoothly into thermoform fill & seal equipment and a flange that seals securely across the package.
- The Style 352 also wins a "seal of approval" with consumers, thanks to an easy-grip flange and easy-close zipper profile for trouble-free handling.

Zipper Specification

Product Description:

STYLE 352 - Soft Seal® Material + ME Sealant

GKL07782-1

GF10 Reusable Spool

GKL07775-1

GF13 Reusable Spool

PROFILE WEIGHT:

3.27 grams/ft +/- 0.1 grams/ft

WIDTH MEASUREMENTS:

28.0 mm +/- 0.3 mm

FOOTAGE/SPOOL:

GF10 Spool: 5,000 ft + 100 - 0 ft

GF13 Spool: 7,000 ft + 100 - 0 ft

SPOOLS/PALLET:

GF10 Spool: 16 spools

GF13 Spool: 12 spools

FOOTAGE/PALLET:

80,000 ft + 1600 - 0 ft

84,000 ft + 1200 - 0 ft

FINISHED SPOOL UNIT WEIGHT:

~43.4 lbs

~56.0 lbs

PACKAGING:

GF10 Spool 10.625" width

1.5" shaft O.D.

19.75" flange O.D.

GF13 Spool 14.0" width

1.5" shaft O.D.

19.75" flange O.D.

PROPERTIES:

Zipper material(s): Soft Seal® material with special sealant

Suitable for food contact applications

Sealing temperature range: **200-280 °F

Holding force from consumer side: 3.0 lbs target avg.

Each spool individually wrapped & placed in individual shipping case.

**Temperature range may vary depending on type of package film used.

Call your Fresh-Lock® zipper representative for details on our Zipper Spool Reuse Program.

www.Fresh-Lock.com



© 2011 Presto Products Company • A Business of Reynolds Packaging Group
P.O. Box 2399 • Appleton, WI 54912-2399
(800) 265-0750 • Fax (920) 738-1347 • E-mail: fresh-lock@reynoldspkg.com

